



Raised temperature resistant hydronic heating tubing

BOW's multi-layer OXYPERT® tubing is BOW's response to an increasing popular demand for high performance materials that meet the ever complicated and wide ranging needs of our customers.

BOW OXYPERT® tubing is an ideal choice.

- Resistant to raised temperature
- With oxygen outer barrier liner
- Designed for circulation heating applications such as radiant slab heating system for concrete, snow melting applications and baseboard heating
- Joints can be made with crimp rings and BOW's stainless steel press sleeves
- Great flexibility of the pipe reduces installation cost
- Eco-friendly-recyclable
- Corrosion resistant

BOW OXYPERT PIPE

NOMINAL DIMENSION	O.D. DIMENSION	ITEM	LENGTHS	QTY /PKG	QTY CRATE	PRICE PER 100'
1/2"	.625	578674	12'	300	13,500	170.29
		578492	20'	500	20,000	170.29
3/4"	.875	578682	12'	120	6,600	297.32
		578567	20'	200	10,000	297.32
NOMINAL DIMENSION	O.D. DIMENSION	ITEM	COILS	QTY /PKG	QTY CRATE	PRICE PER 100'
1/2"	.625	578500	100'	100	5,000	170.29
		578518	250'	250	7,500	170.29
		578526	300'	300	9,000	170.29
		578534	500'	500	6,500	170.29
		578542	1000'	1,000	8,000	170.29
		578559	1200'	1,200	8,400	170.29
3/4"	.875	578575	100'	100	4,000	297.32
		578583	250'	250	3,750	297.32
		578591	300'	300	4,500	297.32
		578609	500'	500	5,000	297.32
		578617	1000'	1,000	5,000	297.32



ASTM F2623

